TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 10.11.2026



(slika je simbolična)

vžigalne erozija zaščiten PU cevi, cevi Ø 6x4, rola 25 m

Kategorija: Anti-spark PU hose
Šifra: **113879RIE**

Kratek opis

Spark erosion protected PU hose, Temperature range -40 °C to 70 °C, Hose Ø 6x4, Working pressure 5 - 12 bar, Roll of 25 m
Blue polyurethane hose with an outer sheath made of black synthetic resin material.
This sheath protects the inner PU tube from welding sparks. The sheath is not attached to the inner tube and can therefore be easily removed to enable conventional fittings to be installed.
- Protects against welding sparks
- Extremely flexible and non-kinking
- Resistant to a large number of chemicals, oils, greases, acids, bases, heat, ageing, UV light

Tehnične Specifikacije

Min. temperaturno območje [°C]	-40
Barva	black
I.D. cevi [mm]	4
Min. delovni tlak [bar]	5
O.D. cevi [mm]	6
Max. delovni tlak [bar]	12
Min. polmer upogibanja [mm]	12.7
Dolžina koluta [m]	25
Max. temperaturno območje [°C]	70