



Vzmetni bat, sesalni priključek G 1/8 ET, hod vzmeti 50 mm

Kategorija: [Spring plungers](#)
Šifra: **108541RIE**

(slika je simbolična)

Kratek opis

Spring plunger, Suction / vacuum connection G 1/8 ET, G 1/8 IT, Spring travel 50 mm, Operating temperature 0 °C to 80 °C

Suitable for all round or oval suction pads in our standard range.

Applications:

- Handling workpieces with different heights (such as curved metal sheets, etc.)
- Handling easily damaged workpieces, since the plunger ensures soft placement

Type

- Spring plunger consisting of a high-strength steel rod, guide sleeve and lower damping spring
- Plunger rod with integrated vacuum feed

Tehnične Specifikacije

| | |
|-------------------------------|----------|
| Dovod vakuuma | G 1/8 IT |
| Navoj na sesalni blazini | G 1/8 ET |
| Vzmetna stopnja [N/mm] | 0.097 |
| Zategovalnik vzmeti [N] | 2.92 |
| Sila vzmeti [N] | 5.34 |
| Pot vzmeti [mm] | 50 |
| Max. delovna temperatura [°C] | 80 |
| Teža [g] | 110.0 |
| Dolžina [mm] | 124.0 |
| Vodoravna obremenitev [N] | 173 |
| Vertikalna obremenitev [N] | 3700 |