

Datum: 02.06.2026



## Zadnji splakovalni za pitno vodo, preizkušen na DVGW, R 3/4

Kategorija: [Back-flushing filters](#)  
Šifra: **101409RIE**

(slika je simbolična)

### Kratek opis

Back flush filter for potable water, DVGW tested, 90 µm to 110 µm, R 3/4, Input pressure max. 16 bar  
For filtering drinking and domestic water in addition to well, process and cooling water for once-through cooling systems. These filters protect the water pipes and all water-carrying parts of the system on the downstream side against malfunctions and corrosion damage.  
The filter candle must be cleaned manually at regular intervals by back-flushing (flushing out dirt particles).  
Integrated back-flushing element with suction elements, back-flushing lever, wing lever for back-flushing element, hose connection for flushing water.

### Tehnične Specifikacije

|   |                                       |
|---|---------------------------------------|
| Cedilna košarica                        | Impact-resistant plastic              |
| Merjenje pretoka                        | At pressure drop $\Delta_p =$ 0.2 bar |
| Navoj                                   | R 3/4                                 |
| Ohišje                                  | Brass                                 |
| Pretok KVS vrednost [m <sup>3</sup> /h] | 3                                     |
| Min. sobna temperatura [°C]             | 5                                     |
| Min. temperatura vode [°C]              | 5                                     |
| Max. vhodni tlak [bar]                  | 16                                    |
| DN                                      | 20                                    |
| Max. temperatura vode [°C]              | 30                                    |
| Max. sobna temperatura [°C]             | 40                                    |
| A [mm]                                  | 80.0                                  |
| Rang filtra [µm]                        | 90                                    |
| Spodnja širina mrežice [µm]             | 110                                   |
| B [mm]                                  | 184.0                                 |
| C [mm]                                  | 352.5                                 |