
TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 11.11.2026



(slika je simbolična)

Zaporni ventili manometrov, pipa - rotirajoča puša, G 1/2

Kategorija: Wika
Šifra: **102655RIE**

Kratek opis

Block valve pressure gauge, Taps - rotating bushing, bright brass, G 1/2, PN 25 bar, AF 27, max. 50 °C, Test flange 60x25x10
It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe.
When the lever is set to the »blow out« position, the medium is discharged into the atmosphere.
Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Tehnične Specifikacije

Aplikacije	For all pressure gauges with a flat gasket acc. to DIN 16258
Navoj	G 1/2
Ohišje	Brass with a bare metal surface
Različica	male / loose (rotatable) female, with test flange 60x25x10
Ročica	Plastic
PN [bar]	25
a/f [mm]	27
Max. temperaturno območje [°C]	50
Testna prirobnica	60x25x10