TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 26.11.2026

Zaporni ventili manometrov, pipa - vpenjalni tulec, G 1/4



Kategorija: Wika
Šifra: **102656RIE**

(slika je simbolična)

Kratek opis

Block valve pressure gauge, Taps - tension sleeve, bright brass housing, steel tension sleeve, G 1/4, PN 6 bar, AF 17, max. 50 °C
It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe.
When the lever is set to the »blow out« position, the medium is discharged into the atmosphere.
Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Tehnične Specifikacije

Aplikacije	For all pressure gauges with a flat gasket acc. to DIN 16258
Konektor z notranjim/zunanjim navojem	Phosphatised steel
Navoj	G 1/4
Ohišje	Brass with a bare metal surface
Različica	male / female/female
Ročica	Plastic
Standard	DIN 16262-B
PN [bar]	6
a/f [mm]	17
Max. temperaturno območje [°C]	50