

Datum: 23.05.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

Zaščitna spojka s tipko z N.N.I.D. 6, ISO 6150 C, G 1/8 N.N.

Kategorija: [Pushbutton safety coupling DN 6, female](#)
Šifra: **141926RIE**

Kratek opis

Pushbutton safety coupling I.D. 6, ISO 6150 C, Stainless steel, G 1/8 IT, Operating pressure max. 12 bar, Temp. -20 °C to 200 °C

"

High quality, robust and long-lifetime quick connect coupling in a safety design that can be operated with one hand.

When pushed for the first time the coupling is vented, the plug remains securely in the coupling.

After a second push the plug is released.

This prevents a potential "whiplash effect" and the risk of operating personnel is practically excluded.

The safety version meets ISO standard DIN EN ISO 4414.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining, offshore.

"

Tehnične Specifikacije

| | |
|--------------------------------|---------------------------------|
| Min. temperaturno območje [°C] | -20 |
| Gumb | Stainless steel |
| Merjenje pretoka | at 6 bar and $\Delta p = 1$ bar |
| Navojni kos | Galvanised steel |
| Ohišje | Stainless steel |
| Povezava | G 1/8 IT |
| Tesnilo | FKM |
| Ventil | Brass |
| Vtični profil | acc. ISO 6150 C |
| Vzmet | Stainless steel |
| DN | 6 |
| Max. obratovalni tlak [bar] | 12 |
| a/f [mm] | 20 |
| Dolžina [mm] | 53.0 |
| Max. temperaturno območje [°C] | 200 |
| Pretok | 1150 l/min (air) |