

Datum: 05.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## Zaščitna spojka s tipko z Z.N.I.D. 6, ISO 6150 C, G 1/2 Z.N.

Kategorija: [Pushbutton safety coupling DN 6, male](#)  
Šifra: **141933RIE**

### Kratek opis

Pushbutton safety coupling I.D. 6, ISO 6150 C, Stainless steel, G 1/2 ET, Operating pressure max. 12 bar, Temp. -20 °C to 200 °C

High quality, robust and long-lifetime quick connect coupling in a safety design that can be operated with one hand.

When pushed for the first time the coupling is vented, the plug remains securely in the coupling.

After a second push the plug is released.

This prevents a potential "whiplash effect" and the risk of operating personnel is practically excluded.

The safety version meets ISO standard DIN EN ISO 4414.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining, offshore.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Gumb	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 1$ bar
Navojni kos	Galvanised steel
Ohišje	Stainless steel
Povezava	G 1/2 ET
Tesnilo	FKM
Ventil	Brass
Vtični profil	acc. ISO 6150 C
Vzmet	Stainless steel
DN	6
Max. obratovalni tlak [bar]	12
a/f [mm]	22
Dolžina [mm]	58.0
Max. temperaturno območje [°C]	200
Pretok	1150 l/min (air)